


RESIDENTIAL SOLID CORE

RPC 001



TOP RAIL Standard "2 1/4" thick, using solid softwood

VERTICAL STILES Standard 1" thick, using solid or fingerjoint softwood

CORE Low-density particle board, specifically designed for door core; Mat-formed 28 to 33 per cubic foot; meets or exceeds ANSI A208.1-1998; Grade I-LD-1 or I-LD-2

FACE All commercially available species veneers with Premium 'A' grade face, medium-density overlay, or tempered hardboard

BOTTOM RAIL Standard 2 1/4" thick, using solid softwood

WIC CERTIFIED & WDMA PREMIUM GRADE DOOR

DOOR STANDARDS:

- **Neutral pressure** 20-minute ITS/ Warnock-Hershey or U.L. fire labels shall be available within size and usage limitations. Fire-rated doors must use approved light frames. Louvers are prohibited in 20-minute fire doors. Neutral pressure must be noted at time of bid.
- **Positive Pressure** fire label is available on 20-minute single doors going into welded or knockdown steel frames. Surfaced-applied smoke gasketing, such as Pemko S88, must be applied to achieve "S" rating (gasketing to be supplied by others). Listed and labeled steel light frames must be used for light openings. Positive pressure must be noted at time of bid.
- **Hardware preparation:** All cutouts for mortise hardware shall be made at the factory from hardware manufacturer's templates and approved shop drawings.
- **Size & Thickness:** Doors shall be $1\frac{3}{4}'' \pm 1/16''$ thick, and of sizes and designs as indicated on the drawings and schedules. Dimensions indicated are prior to factory trimming and prefitting.



DOOR FEATURES:

Maximum Size	4/0 X 9/0 singles, 8/0 X 9/0 pairs
Available Thickness	1 3/8", 1 3/4" and 2 1/4"
Stiles	Standard 1" thick, using solid softwood or fingerjoint softwood, minimum 13/16" thick, centerline of bevel
Cutouts	Allow 5" minimum distance from door edges and hardware cutouts, not to exceed 40 percent of door surface.
Standard Bevel	1/8" in 2"
Glue	Type I
Veneer Match	Book match standard. Slip or random available if specified (pair & set match). Others available upon request.
Fire Labeling Options	20 Minute 'S' Label, Positive Pressure CAT-A labels available
Warranty Information	Lifetime interior warranty. One-year warranty available for exterior applications. See warranties for further details.